



Enjoy High Voice quality IP Phone, iPECS LIP-9000 Series

Enjoy a wide selection of easy-to-use system IP phones to enrich your communications experience with a powerful speaker phone and wideband voice support. There are 5 types of phones from Entry level to Advanced terminals, designed to best fit the users' business needs. The Ericsson-LG Enterprise proprietary protocol provides fully integrated system features just like the conventional features in rich PBX solution.

LIP-9040

Advanced

Suitable User

- Managers, Remote workers

Key Features

- UC enabled (IM Presence)
- 12(X3 page, total 36) flexible buttons
- Wide Gray scale graphic type 8 line LCD w/ backlit



LIP-9030

Professional

Suitable User

- Managers, General office, Remote workers

Key Features

- UC enabled (IM Presence)
- 8(X3 page, total 24) flexible buttons
- Wide Gray scale graphic type 6 line LCD w/ backlit



LIP-9020

Standard

Suitable User

- General office, Remote workers

Key Features

- 10 flexible buttons
- Wide Gray scale graphic type 4 line LCD w/ backlit



LIP-9010

Basic

Suitable User

- Small office, Remote workers, Receptionists

Key Features

- 5 flexible buttons
- Wide Gray scale graphic type 3 line LCD w/ backlit



LIP-9002

Entry

Suitable User

- Reception lobbies and meeting areas
- Manufacturing and retail floors

Key Features

- 4 flexible buttons
- Affordable large deployment with wideband voice



ACCESSORY

LIP-9012DSS

- 12 keys w/ triple color LED
- Paper underlay
- Power via keyset



LIP-9024DSS

- 24 keys w/ triple color LED
- Paper underlay
- Power via keyset



LIP-9024LSS

- 12 keys and 2 page button w/ triple color LED
- LCD underlay
- Power via keyset



Bluetooth Module (LIP-9000BTMU)

- Optional module
- Bluetooth V2.1+EDR
- Speakerphone or handset calls on smart phone and Bluetooth headset



LIP-9000 Series

	LIP-9002	LIP-9010	LIP-9020	LIP-9030	LIP-9040	
Display	LCD Size (Pixels)	128 X 32	320 X 48	320 X 80	320 X 112	320 X 144
	LCD Dimension (W*H mm)	63.4 x 13.1	94.5 x 18.0	94.0 x 29.6	94.0 x 37.4	94.0 x 47.0
	UI Line	2 Line	3 Line	4 Line	6 Line	8 Line
	Backlit	N/A	YES			
	LCD Type	Black and white	Gray scale graphic			
Keypad	- Programmable button with BLF	YES (4)	YES (5)	YES (10)	YES (8X3 page, total 24)	YES (12X3 page, total 36)
	- Softkey	N/A		YES (3)		
	- Navigation key	N/A	YES			
	- Fixed button (dedicated hard keys)	YES (10 buttons)	YES (12 buttons)			
	- LED Buttons	YES (3 Color LED)				
Network Interfaces	Ethernet (IEEE 802.3/1 Gigabit)	YES (2*10/100 Base-T)		YES (2*10/100/1000Base-T)		
	Bluetooth (LIP-9000BTMU)	N/A	YES (External Bluetooth Dongle)			
	EHS	N/A	External EHS			
Speaker	YES (Half duplex)		YES (Full duplex)			
Audio interfaces	Handset (RJ-9)	YES				
	Headset (RJ-9)	YES				
XML*	N/A	YES				
IM Presence	N/A			YES		
Power	Local(Optional - 48V, 0.3A)	YES				
	PoE (802.3af)	YES (Class 1)		YES (Class 1 /wo Button Kit, Class 2 /w Button Kit)		
	Codec	G.711, 729AB & 722				
Audio	Call Signaling Protocol	Ericsson-LG Enterprise iPECS protocol				
	Features	Echo cancellation, VAD, CNG, Hearing Aid Compatible				
	IP Address	Static/ DHCP				
Network	LLDP-MED, VLAN	YES				
	QoS	Dynamic jitter buffering, 802.1p/Q, Layer 3 TOS, DiffServ				
	Standard	SRTP w/AES-128, 802.1x/EAP-MD5(EAPOL), Password login				
Security	VPN (OpenVPN)	YES				
	Auto/ Remote upgrade	YES				
Management	Web Management	YES				
H/W Spec.	Acctive / Standby Power consumption (Watt)	1.93/ 1.80	1.93/ 1.80	2.45/ 2.05	2.75/ 2.35	2.52/ 2.10
	Dimension (HxWxD, mm)	108x195x229	126.2x214.3x229	126.2x214.3x229	126.2x228.9x229	126.2x228.9x229
	Weight (Net, g)	575	690	737	767	767
	Phone tilting	N/A	YES (2 Level Bracket)			
Others	Button kit Support	N/A		YES (LIP-9012DSS/24DSS/24LSS)		
	Wall mount	YES (Optional)				
	Ring type	Wave file/FM method				
	Major features	Speed dialing, Redialing, Call holding, Call waiting, Call park/Call pick up, Call forwarding, Conference call, Volume up/down control, Caller ID, Distinctive ring/Multi-ring, Multi-lines, Direct mail/Messaging access, Directory/Phone book and full system features				

* XML : XML is supported in case of CM SIP only

DSS/LSS Option

Model	LIP-9012DSS	LIP-9024DSS	LIP-9024LSS
Compatibility	LIP-9020/ LIP-9030/ LIP-9040		
Flexible Button	12	24	12 X 2 page, Total 24
Underlay Type	Paper	Paper	LCD
Maximum Connection	1		
Triple Color LED	YES		
External Power	N/A		

Bluetooth Module (LIP-9000BTMU)

Hardware Specifications

- CPU : CRONUS 32 Bit CPU(ARM9, Max. 200MHz Core)
- Class 2 Level Output Power Available (Max. 4dBm)
- Bluetooth v2.1 + EDR
- Up to 10 meters range
- Master (for Headset) / Slave (for Smartphone) Mode support

Product Features

- Connect with BT Headset or Smart phone(Master or Slave operation)
- Bluetooth Pairing: Bluetooth device searching, Pairing list display, Pairing and connecting

- Headset Profile, Hands free Profile, Phonebook Profile, FTP profile
- Phonebook: Max 3000 contacts, Max 1 MB (Size)
- FTP speed: 40 Kbps
- Volume steps: 11 steps
- Support Rings: 8
- Sound path switching between handset and Bluetooth Headset
- Audio switching between smart phone and IP Phone
- Support upgrade of LIP-9000BTMU : Upgrade via Bluetooth
- Display CID of smart phone
- Enhanced Bluetooth compatibility : BT Headset, Smart phone

The content of this document is subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson-LG Enterprise shall have no liability for any error or damage of any kind resulting from the use of this document

© Ericsson-LG Enterprise Co., Ltd. 2015 Ver. 1.2

Ericsson-LG Enterprise Co., Ltd.
 (431-749) 77, Heungan-daero 81 beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, South Korea
www.ericssonlg-enterprise.com | www.iPECS.com

iPECS is an Ericsson-LG Brand

